



## 800 PERMANENT ASPHALT REPAIR

### Imco® Permanent Asphalt Repair

‘READY TO USE.’

‘NO PRIMER REQUIRED’

Our unique, one product formulation is designed to achieve optimum performance year round in all environmental conditions.

#### Uses:

Will effectively and permanently repair pot holes during wet, freezing or extreme heat conditions.

#### Features:

Unique formulation premixed and ready to use.

No heating or tacking required

Adheres to asphalt, concrete and steel

Permanent, no milling or patch release  
Permanent repair = Cost effectiveness

Convenient packaging for all repairs

- 50 pound bags
- 5 gallon pails
- 55 gallon drums.

Easy 3 step repair

Backed by Imco’s® strict quality controls

Testing at independent laboratories

Available at Quality Selected Dealers

#### Technical Data

Asphalt Content: ASTM D2172-92 5.2%

Static Stripping: ASTM D1664-80 95-100%

Kinetic Stripping: OPSS 1153-02-01 95%

#### Preparation

Clean out any loose chunks or debris using a stiff broom or blower.

#### Application

Place Permanent Asphalt Repair by Imco® in hole—layer 3 inches at a time.

Compact with a tamper, roller or vehicle. Repeat until hole is filled to the desired thickness.

To reduce tacky surface dust with sand or cement.

Open to traffic immediately

#### Q & A

Shelf life— one year

Seasonal grades— NO

One Year Round grade

Set up time— Immediate

Coverage— 10 pounds per square foot at 1 inch deep. 1.4 tons per cubic yard.

Safety— MSDS available on request at [www.imcotechnologies.com](http://www.imcotechnologies.com)